

Bookstack

```
version: '3'

services:

  bookstack:
    image: ghcr.io/linuxserver/bookstack:latest
    volumes:
      - bookstack:/config
    ports:
      - "8001:80"
    restart: unless-stopped
    environment:
      DB_USER: bookstack
      DB_PASS: RD4!JelP4grTqVGjr
      DB_DATABASE: bookstack
      DB_HOST: db:3306
      APP_URL: http://192.168.1.12:8001
    depends_on:
      - db

volumes:
  bookstack:
```

Avec Traefik

```
version: '3'

services:

  bookstack:
    image: ghcr.io/linuxserver/bookstack:latest
    container_name: bookstack
    restart: unless-stopped
```

```
networks:
  - traefik
environment:
  DB_USER: bookstack
  DB_PASS: RD4!JelP4grTqVGjr
  DB_DATABASE: bookstackapp
  DB_HOST: db:3306
  APP_URL: http://ndd.fr
volumes:
  - bookstack:/config
labels:
  - "traefik.enable=true"
  - "traefik.http.routers.bookstack.rule=Host(`ndd.fr`)"
  - "traefik.http.routers.bookstack.entrypoints=web"
depends_on:
  - db

volumes:
  bookstack:

networks:
  traefik:
    external: true
```

Activation MAIL()

Ajouter les variables suivantes dans le fichier docker-compose.yml

```
MAIL_HOST: smtp.**.fr
MAIL_USERNAME: **@orange.fr
MAIL_PASSWORD: ***
MAIL_PORT: 25
MAIL_FROM: admin@bookstack.fr
MAIL_FROM_NAME: notification
```

Revision #2

Created 10 March 2024 09:59:46 by Dunnload

Updated 16 March 2024 12:28:50 by Dunnload